

24 channel Analogue IC Tester Module

V-I test capability

Number of test channels:	24 + 2 probes and references
Test voltage:	2 V to 50 V peak to peak
Voltage resolution:	8 to 12 bits
Test frequency:	37.5 Hz to 12 kHz
Test current:	1 μ A to 150 mA
Source impedance:	100 Ohm to 1 M
Test waveforms:	Sine, square, triangle, ramp, pulse
Waveform modes:	V-I, V-T, I-T
Waveform display:	Multi-plot with single waveform zoom
Waveform comparison:	Automatic comparison algorithm for good and bad boards using live probes or disk
V-I comparison tolerance:	50 mV to 500 mV with 50 mV resolution
Package support:	DIL, SOIC, PLCC, QFP and variants with MultiProbes
Pulse output:	Positive, negative or bipolar for thyristors/triacs
Pulse amplitude:	Adjustable to +/-10 V
Calibration:	Can be calibrated by user

Analogue functional test capability

Number of I/O channels:	24 independent including 3 special discrete channels
Driver voltage:	-12 V to +12 V
Driver voltage resolution:	10 bit
Driver output current:	200 mA max sink or source
Driver states:	Voltage source, current source, off
Discrete source current:	10 μ A - 150 mA. (driving a load returned to 0 V)
Driver source impedance:	34 Ohm (34 Ohm, 1 k or 10 k on discrete channels)
Sensor input voltage:	+/- 24 V
Sensor voltage protection:	+/- 50 V
Sensor input impedance:	2 M
Sensor voltage resolution:	12 bit
Restrict voltage:	-10 V to +10 V
Restrict voltage resolution:	8 bit
Sensor current measurement:	1 mA to 150 mA (10 nA to 150 mA on discrete channels)
Sensor current resolution:	12 bit
Sensor current input impedance:	50 Ohm (50 Ohm, 1 k, 10 k or 1 M on discrete channels)
Short detection threshold:	<4 Ohm
Link detection threshold:	<10 Ohm
Test modes:	Single, unconditional loop, pass loop, fail loop
Test clip positioning:	Automatically adjusts for clip orientation
Circuit compensation:	Automatically modifies test for IC/PCB connections
Test trace:	Test waveforms and voltages displayed
Test analysis:	Displays test parameters such as gain, hfe, feedback
IC test capability:	Op-amps, comparators, DACs, ADCs, switches and special function analogue ICs in- or out-of-circuit
Discrete test capability:	Transistors, FETs, thyristors, triacs in- or out-of-circuit
IC test libraries:	Analogue, discrete, package, user
Result comparison:	Results can be saved for good/bad board comparison
Package support:	DIL, SOIC, PLCC and variants with MultiProbe kits
SLIM test programming:	Structured programming language for

library additions

Other specifications

Electrical input:	(typical) +12 V, 1 A (max) (typical) -5 V, 750 mA (typical) -12 V, 100 mA
Dimensions:	147 x 202 x 42 mm
Weight:	1 kg

Accessories

Standard	1 x SMD test tweezer set and adapters 1 x 24 way test clip and cable assembly 1 x Blue V-I probes and adapter 1 x Yellow V-I probes and adapter 2 x Pulse leads 2 x Ground leads 3 x Discrete leads
----------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Options

Internal fitting	PCI interface
External fitting	MultiLink case (cost option) with serial or parallel connection External case (cost option) which can hold up to 4 SYSTEM 8 modules.

The ABI development team strive continually to improve their products for the benefit of the customer. The specification of current products may therefore vary from that described in this brochure.



Making Light Work

ABI Electronics Limited
Dodworth Business Park
Dodworth, Barnsley
South Yorkshire S75 3SP
United Kingdom
Tel: +44 1226 207420
Fax: +44 1226 207620
www.abielelectronics.co.uk