

8200LN

Rubidium Oscillator



Key Features

- 10 MHz Output
- 1 PPS Output
- 1 PPS Input
- Low Phase Noise
- Low Physical Profile (< 1.0" high)
- Low Weight <2 lbs.
- Digital Monitor and Control
- Shock/Vibration Hardened

Optional Features:

- 5 MHz Output
- Low-g sensitivity

Key Benefits:

- Superior frequency stability
- Diverse environmental conditions support

The Microsemi® 8200LN is a ruggedized rubidium oscillator designed for ground tactical, shipboard and airborne applications where superior frequency stability under diverse environmental conditions is required. Advanced communications, navigation and targeting systems require precision oscillators that can withstand a wide range of operating environments with minimal degradation in frequency accuracy and stability. The 8200LN support these applications with superior phase noise and excellent short and long term frequency stability.

The 8200LN is unique in that it combines excellent frequency stability and low dynamic phase noise in a small, low profile package measuring less than 1.0 inches high and weighing less than 2 lbs.

The standard performance 8200LN provides both 10MHz and 1PPS outputs along with a 1PPS input for disciplining to a GPS receiver or other primary standard. Optional configurations can support additional outputs or custom outputs. When equipped with an optional low g sensitivity crystal, the 8200LN can maintain low phase noise performance over a wide range of vibration profiles. The 8200LN is designed around proven rubidium and OCXO technology that has been deployed in numerous airborne, shipboard and ground tactical platforms for over thirty years.

8200LN

Specifications

ELECTRICAL SPECIFICATIONS

• RF Output

| | |
|-------------------------|---|
| Frequency: | 10 MHz (nominal) |
| Format: | Sinewave |
| Amplitude: | +10 dBm \pm 2 dBm (0.7 V rms nominal) |
| VSWR | 1.5:1 |
| Harmonic Distortion | < -30 dBc |
| Non-harmonic Distortion | < -80 dBc |
| Load Impedance: | 50 ohms @ 10MHz |
| Connector: | SMA Female |
| Qty: | 2 |

• 1PPS Output

| | |
|-------------------|-----------------------|
| Rise Time: | <5 ns |
| Pulse Width: | <400 ns +/-10% |
| Level: | >3 Vdc TTL Compatible |
| Jitter: | <10 ps RMS |
| Output Impedance: | 50 ohms |
| Connector: | SMA Female |
| Qty: | 2 |

PERFORMANCE PARAMETERS

• Phase noise [SSB], E(f), dBc/Hz (Static)

| | | |
|---------|--------|-------|
| SB Freq | 10 MHz | 5 MHz |
| 1 Hz | <-98 | <-103 |
| 10 Hz | <-130 | <-135 |
| 100 Hz | <-148 | <-153 |
| 1 KHz | <-154 | <-155 |
| 10 KHz | <-157 | <-157 |

• Spectral purity

| | |
|----------------|----------|
| Harmonics: | <-40 dBc |
| Non-harmonics: | <-80 dBc |

• Aging

| | |
|--------------------------|-----------------|
| Monthly (after 1 month): | < \pm 5.0E-11 |
|--------------------------|-----------------|

• Frequency accuracy at shipment:

| | |
|--|----------------------------|
| | < \pm 5.0E-11 (@ +25° C) |
|--|----------------------------|

• Frequency retrace

| | |
|--|--|
| | < \pm 5.0E-11 (on-off-on: 24 hours, 24 hours, 24 hours @ 25°C) |
|--|--|

• Short term stability σ_y (r) (Allan deviation)

| | |
|--------------|----------|
| τ (sec) | |
| 1 | <1.4E-11 |
| 10 | <7.0E-12 |
| 100 | <2.5E-12 |

• Frequency control

| | | |
|--------------------------|---|--------|
| Analog freq. adj. range: | +/-1.5E-9, 0 - 5V into 5Kohm impedance (optional) | |
| Digital freq. adj. res: | +/-1.0E-6 with 1.0E-12 resolution | |
| Warm-up times | -40° C | +25° |
| Time to lock: | <8 min | <6 min |
| Time to <1E-9: | <10 min | <8 min |
| Power Consumption @ 28V: | <28W | <28W |

• Input voltage range:

| | |
|--|---------------|
| | +15 to 32 Vdc |
|--|---------------|

(Protected against reverse polarity & transients)

• Voltage sensitivity:

| | |
|--|--------------|
| | <5.0E-12 Vdc |
|--|--------------|

(\pm 10% voltage change from nom. 28 Vdc Input)

• Input power, quiescent:

| | |
|----------------------------|------|
| +28 Vdc @ -40° C baseplate | <20W |
| +28 Vdc @ +25° C baseplate | <15W |
| +28 Vdc @ +75° C baseplate | <11W |

• Lock Status (BITE)

| |
|-------------------|
| TTL low = Lock |
| TTL high = Unlock |

• RS-232 control/monitor interface

Provides ID, status/monitor information, and frequency/operating parameter adjustments. Protocol: 9600, 8, 1, None, No flow control.

ENVIRONMENTAL & PHYSICAL SPECIFICATIONS

• Temperature

| | |
|------------------------|-------------------------------|
| Operating: | -40° C to +75° C baseplate |
| Storage: | -55° C to +95° C |
| Frequency Sensitivity: | <3.0E-10 over op. temp. range |

• Thermal shock (non-operating):

MIL-STD-202, Method 107, Test Condition A, 10 cycles -55° C to 85° C

• Orientation sensitivity:

| | |
|--|------------------------------|
| | <5.0E-11 for any orientation |
|--|------------------------------|

• Pressure sensitivity:

| | |
|--|---------------|
| | <1.0E-13/mbar |
|--|---------------|

• Altitude

| | |
|----------------|---------------------------------|
| Operating: | Sea level to 40,000' (12,192 m) |
| Non-operating: | Sea level to 80,000' (24,384 m) |

• Magnetic field sensitivity:

| | |
|--|----------------------------|
| | (DC field, \leq 2 Gauss) |
|--|----------------------------|

$\leq \pm 4.0E-11$ /Gauss

• Relative humidity (operating):

0 to 95% RH per MIL-STD-810, Method 507.4

• Salt fog:

MIL-STD-810, Method 509.4

• Vibration:

MIL-STD-810, Method 514.5, Procedure I

Operating: Category 24, Minimum Integrity, 7.7 grms @ 0.04 g/Hz, 20 Hz -1KHz, 15 min/axis (maintain frequency lock)

Non-Operating: Category 24, Minimum Integrity, 15.4 grms @ 0.16 g/Hz, 20 Hz -1KHz, 30 min/axis

• Shock:

| | |
|----------------|--|
| Operating: | MIL-STD-202, Method 213 |
| Non-Operating: | 30g, 11ms, half-sine impulse (maintain frequency lock) |

50g, 11ms, half-sine impulse

• EMI MIL-STD-461

| | |
|-----------------|---------------------|
| Emissions: | CE102, RE102 |
| Susceptibility: | CS101, CS114, RS103 |

• MTBF:

70,000 hours (ground fixed)

@ +40° C baseplate

• On-Off cycling endurance:

5000 cycles at 10° C baseplate

• Reliability Specification:

MIL-HDBK-217F

• Input Connector:

(1) DB-9 (All input power)

(1) DB-9 (All monitoring)

• Reliability Specification:

MIL-HDBK-217F

• Dimensions

| | |
|---------|-------|
| Height: | 0.95" |
| Width: | 6.13" |
| Depth: | 5.52" |

Volume: 32.2 in3

Weight: <2.0 lbs



Microsemi

Microsemi Corporate Headquarters
One Enterprise, Aliso Viejo, CA 92656 USA
Within the USA: +1 (949) 380-6100
Sales: +1 (949) 380-6136
Fax: +1 (949) 215-4996

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor solutions for aerospace, defense and security; enterprise and communications; and industrial and alternative energy markets. Products include high-performance, high-reliability analog and RF devices, mixed signals and RF integrated circuits, customizable SoCs, FPGAs, and complete subsystems. Microsemi is headquartered in Aliso Viejo, Calif. Learn more at

www.microsemi.com

©2014 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

DS/8200ln/061014 900-00497-000 B